

EMULGANTE CO-

Technical Data Sheet No. 2105 – March 2020



Distribuito da:




Tellerini s.p.a.

Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it

Product Description

EMULGANTE CO-5 is a fatty alcohol polyethyleneglycol ether, based on cetyl-oleyl alcohol and ethylene oxide (about 5 moles). It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



CAS registry no. 68920-66-1
EINECS no. 931-991-6
INCI OLETH-5

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	Visual	-	Cloudy liquid
√ Cloud point (20+100 BDG at 25%)	RCM 3646	°C	63 – 67
√ pH (5%)	RCM 3645	-	5,0 – 7,0


√ value reported on inspection certificate.

¹ specification No. 3023 rev. 2 of April 30th 2008.

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content	Calculated	%w/w	45
HLB	Calculated	-	8,9
Hydroxyl number	EN 13926	mg KOH / g	120
Average Molecular weight	Calculated	g/mol	470
Pour point	ASTM D 97	°C	17
Viscosity at 50°C	ASTM D7042	cSt	19
Density at 50°C	ASTM D7042	kg/m ³	925
Flash point	ASTM D 93	°C	> 125

RCM are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



sasol

EMULGANTE CO-5

Technical Data Sheet No. 2105 – March 2020

Main Applications

EMULGANTE CO-5 is used as intermediate to produce textile auxiliaries

Due to its medium HLB value, EMULGANTE CO-5 is mainly used as emulsifier agent for W/O and O/W emulsions for mineral oil, hydrocarbons and fats for metal working and cutting fluid, often in combination with lower HLB emulsifiers like the EMULGANTE CO-2.

Handling and Storage

EMULGANTE CO-5 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

EMULGANTE CO-5 is a cloudy liquid at room temperature and it becomes homogeneous and transparent at temperature higher than 40°C.

At room temperature EMULGANTE CO-5 is not water soluble.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

EMULGANTE CO-5 is generally supplied in drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of companies, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

The information contained in this document is based on Sasol's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products. All our business transactions are governed exclusively by our General Business Terms.