

MARLON NA 55 H

Technical Data Sheet No. 4028 – November 2025

SASOL



Distribuito da:




Tellerini s.p.a.

Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it

Product Description

MARLON NA 55 H is the sodium salt of linear alkyl benzene sulphonic acid. Linear alkyl benzene sulphonic acid of SASOLAB C12 H linear alkyl benzene, is diluted with water and neutralized with sodium hydroxide up to neutral pH.

It is manufactured in Terranova dei Passerini (Lodi, Italy) plant. The chemical structure is the following:



CAS registry no. 68411-30-3
EINECS no. 270-115-0
INCI- name SODIUM C10-13 ALKYL BENZENESULFONATE

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	ASTM E284	-	Flowable paste
√ pH (5% active matter)	EN 1262	-	7,0 – 9,0
√ Anionic active matter (MW = 343)	ASTM D3049	% mass	54,5 – 56,5
√ Unsulphonated matter (HPLC)	EN 13273	-	≤ 1,5
√ Colour (5 % active matter)	EN 1557	Klett	≤ 100
√ Sodium Sulphate	ISO 6844	% mass	≤ 0,7
√ Sodium Chloride	ASTM D4458	% mass	≤ 0,1

√ value reported on inspection certificate.

¹ specification No. 7906 rev. 1 of December 5th, 2025.

Additional Properties

Property	Test Method	Unit	Typical Value
Density at 20°C	ASTM D7042	kg/m ³	1.050
Flash point	ASTM D 93	°C	Not applicable as aqueous solution

**sasol**

MARLON NA 55 H

Technical Data Sheet No. 4028 – November 2025

Further information

Heavy metal

Arsenic (As) less than 1 mg/kg	Cadmium (Cd) less than 1 mg/kg
Cobalt (Co) less than 1 mg/kg	Chromium (Cr) less than 1 mg/kg
Copper (Cu) less than 1 mg/kg	Iron (Fe) less than 5 mg/kg
Manganese (Mn) less than 1 mg/kg	Nickel (Ni) less than 1 mg/kg
Lead (Pb) less than 1 mg/kg	Tin (Sn) less than 1 mg/kg
Strontium (Sr) less than 1 mg/kg	Zinc (Zn) less than 1mg/kg

Heavy metal content is periodically checked (ICP method); data given here have to be considered as typical.

Preservative

MARLON NA 55 H is supplied containing a small amount of preservative sufficient for transport and short term storage. If the product is stored for several weeks or months it is necessary to carry out regular check of microbial content. Furthermore careful precautions like clean sampling vessel, sterilized water for dilution, limit prolonged or too often repeated exposure to open air, etc. are necessary to maintain microbiological purity of the product.

Property	Test Method	Unit	Typical Value
Total Aerobic Microbial Count	Eu.Ph. 5.1.4	CFU/g	< 100
Total Yeasts/Moulds Count	Eu.Ph. 5.1.4	CFU/g	< 10

Microbiological control test is periodically done; data given here have to be considered as typical.

Antioxidants

MARLON NA 55 H does not contain any antioxidant.

Pesticides

MARLON NA 55 H does not contain any pesticide.

Product origin

MARLON NA 55 H is manufactured from following raw materials:

- Linear alkylbenzene with synthetic origin
- Sulphur with synthetic origin
- Caustic Soda with synthetic origin

Main Applications

In detergency MARLON NA 55 H is used as high performance anionic surfactant in Heavy Duty Liquid, Heavy Duty Powder, Hand Dish Washing and Industrial Degreasing formulations.



sasol

MARLON NA 55 H

Technical Data Sheet No. 4028 – November 2025

Handling and Storage

MARLON NA 55 H should be stored preferably in stainless steel tanks or plastic receptacles.

MARLON NA 55 H must be stored at temperature below 50°C and avoid exposure to light in order to minimise hydrolysis and darkening phenomena.

Storage tanks must be heated with water warmed at a temperature below 50°C. The use of steam to warm up the product is absolutely prohibited.

At room temperature MARLON NA 55 is a paste that can be pumped and water soluble.

Shelf-life is 8 months from production date for product in its original and sealed packaging.

Packaging

MARLON NA 55 H is generally supplied in plastic drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of companies, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

The information contained in this document is based on Sasol's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products. All our business transactions are governed exclusively by our General Business Terms.