

# EMULGANTE EL

Technical Data Sheet No. 3201 – October 2022



Distribuito da:



Tellerini s.p.a.

Via Bonazzi, 36  
40013 Castel Maggiore (BO)  
Tel: +39 051 6322111  
Fax: +39 051 715380  
[sicurezza@tellerini.it](mailto:sicurezza@tellerini.it)  
[www.tellerini.it](http://www.tellerini.it)

## Product Description

EMULGANTE EL is a castor oil polyethyleneglycol ether, (about 50 moles of ethylene oxide).  
It is manufactured in Terranova dei Passerini (LO) plant.

CAS registry no. 61791-12-6

## Sales Specification

Property	Test Method	Unit	Guaranteed Value <sup>1</sup>
√ Appearance at 25°C	Visual	-	Paste
√ Colour	RCM 3668	Gardner	≤ 5,0
√ Cloud point (1% in water)	RCM 3646	°C	80 – 85
Saponification number	RCM 3820	mg KOH / g	48 – 56
√ pH (5%)	RCM 3645	-	5,0 – 7,0
√ Free Water (Karl Fischer)	RCM 3804	% mass	≤ 0,50

√ value reported on inspection certificate.

<sup>1</sup> specification No. 4050 rev. 2 of November 13<sup>th</sup> 2009.

## Additional Properties

Property	Test Method	Unit	Typical Value
Dioxane	RCM 1124	ppm	< 1.000
HLB	Calculated	-	14,2
Average Molecular weight	calculated	g/mol	3.200
Pour point	ASTM D 97	°C	19
Viscosity at 50°C	ASTM D7042	mPas	107
Density at 50°C	ASTM D7042	kg/m <sup>3</sup>	1.040
Flash point	ASTM D 93	°C	> 125

RCM are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



**SASOL**

# EMULGANTE EL

Technical Data Sheet No. 3201 – October 2022

---

## Main Applications

EMULGANTE EL is used as O/W solubilizer and dispersing agent in industrial applications, in particular as dye equalizing agent for textile auxiliaries.

---

## Handling and Storage

EMULGANTE EL should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

EMULGANTE EL is a paste at room temperature and it becomes homogeneous and transparent at temperature higher than 35°C.

Avoid contact with strong oxidizers, strong acids and strong bases.

Shelf-life is 24 months from production date for product in its original and sealed packaging.

---

## Packaging

EMULGANTE EL is generally supplied in drums, details on available packaging can be obtained from sales department.

---

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

---

### Sasol Italy S.p.A.

Headquarters  
Viale Forlanini, 23  
20134 Milano, Italy  
Phone +39-02 58453 1  
Fax +39-02 58453 285

Technical Customer Support  
Via E. Mattei, 4  
26827 Terranova dei Passerini (LO), Italy  
Phone +39-0377 463 1  
Fax +39-0377 463 226

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of companies, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

The information contained in this document is based on Sasol's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products. All our business transactions are governed exclusively by our General Business Terms.