

LIALET 125-3

Technical Data Sheet No. 1702 – November 2015



sasol

Distribuito da:




Tellerini s.p.a.

Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it

Product Description

LIALET 125-3 is a fatty alcohol polyethyleneglycol ether, based on LIAL 125 and ethylene oxide (about 3 moles). It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



CAS registry no. 106232-83-1
EINECS no. 932-186-2
INCI C12-15 PARETH-3

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	Visual	-	Cloudy liquid
√ Colour	MPL 1002.0	APHA	≤ 50
Physical state chngement	MPL 1001.0	°C	0 – 5
√ Cloud point (10% in BDG at 25%)	MPL 2001.0	°C	53 – 55
√ Hydroxyl number	MPL 1010.0	mg KOH / g	160 – 166
Molecular weight	Calculated	g/mol	338 – 351
Polyethylene glycols	MPL 2002.0	% mass	≤ 2,0
√ pH (5%)	MPL 1007.0	-	5,0 – 7,0
√ Free Water (Karl Fischer)	MPL 1006.0	% mass	≤ 0,10

√ value reported on inspection certificate.

¹ specification No. 2610 rev. 1 of June 1st 2001.

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content	Calculated	%w/w	40
HLB	Calculated	-	8,0
Viscosity at 50°C	ASTM D445 / ASTM D7042	cSt	12
Density at 50°C	ASTM D7042 / ASTM D4052	kg/m ³	920
Flash point	ASTM D 93	°C	> 125

RCM and MPL are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



sasol

LIALET 125-3

Technical Data Sheet No. 1702 – November 2015

Main Applications

LIALET 125-3 is a raw material for preparation of high active matter ethers sulphates aqueous solutions having low viscosity.

Due to its low number of EO (low HLB value), it is mainly used as a co-emulsifier agent for W/O or O/W emulsions in combination with anionic or non-ionic surfactants with high HLB value.

LIALET 125-3 is a lubricant with anti-static properties in spooling of cotton, acrylic and mixed polyesters/cotton yarns.

Handling and Storage

LIALET 125-3 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

LIALET 125-3 is a cloudy liquid at room temperature and it becomes homogeneous and transparent at temperature about 35°C.

LIALET 125-3 becomes a solid wax at temperature lower than 5°C.

At room temperature LIALET 125-3 is not water soluble.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

LIALET 125-3 is generally supplied in drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

This information is based on our present knowledge and experience. but it is not a guarantee of the performance of our products since the conditions of use are not under our direct control.

However, it implies no liability or other legal responsibility on our part, including any existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. All our business transactions shall be governed exclusively by our General Sales Conditions.

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of Companies. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved.