

LORODAC 2-24

Technical Data Sheet No. 1551 – April 2020




Distribuito da:



Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it

Product Description

LORODAC 2-24 is a fatty alcohol polyethyleneglycol ether, based on NAFOL 1214 and ethylene oxide (about 2 moles). It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



CAS registry no. 68439-50-9
EINECS no. 500-213-3
INCI LAURETH-2

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	ASTM E284	-	Cloudy liquid
√ Colour	EN 1557	APHA	≤ 30
√ Cloud point (10% in BDG at 25%)	EN 1890	°C	50 – 52
√ Hydroxyl number	EN 13926	mg KOH / g	192 – 200
Molecular weight	Calculated	g/mol	280 – 292
Polyethylene glycols	EN 12582	% mass	≤ 2,0
√ pH (5%)	EN 1262	-	5,0 – 7,0
√ Free Water (Karl Fischer)	ASTM E203	% mass	≤ 0,10

√ value reported on inspection certificate.

¹ specification No. 2150 rev. 2 of June 12th 2019.

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content	Calculated	%w/w	32
HLB	Calculated	-	6,3
Pour point	ASTM D97	°C	9
Viscosity at 20°C	ASTM D7042	cSt	28
Viscosity at 40°C	ASTM D7042	cSt	10
Density at 20°C	ASTM D7042	kg/m ³	906
Flash point	ASTM D 93	°C	> 125



sasol

LORODAC 2-24

Technical Data Sheet No. 1551 – April 2020

Main Applications

LORODAC 2-24 is a suitable raw material for the production of anionic surfactants, corresponding ethoxysulphates are widely used for both personal care and detergent formulations, due to their relative low skin irritation potential and easy thickening.

Due to its low number of EO (low HLB value), LORODAC 2-24 is mainly used as a co-emulsifier agent for W/O or O/W emulsions in combination with anionic or non-ionic surfactants with high HLB value.

Handling and Storage

LORODAC 2-24 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

LORODAC 2-24 is a cloudy liquid at room temperature and it becomes homogeneous and transparent at temperature about 40°C.

LORODAC 2-24 becomes a solid wax at temperature lower than 9°C.

At room temperature LORODAC 2-24 is not water soluble.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

LORODAC 2-24 is generally supplied in drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of companies, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

The information contained in this document is based on Sasol's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products. All our business transactions are governed exclusively by our General Business Terms.