

TRIDAC ISO-8

Technical Data Sheet No. 1654 – March 2023



Distribuito da:



Tellerini s.p.a.

Via Bonazzi, 36

40013 Castel Maggiore (BO)

Tel: +39 051 6322111


Fax: +39 051 715380

sicurezza@tellerini.it

www.tellerini.it

Product Description

TRIDAC ISO-8 is a fatty alcohol polyethyleneglycol ether, based on MARLIPAL 13 and ethylene oxide (about 8 moles). It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



CAS registry no. 69011-36-5
EINECS no. 931-138-8
INCI TRIDECETH-8

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	ASTM E284	-	Cloudy liquid
√ Colour	EN 1557	APHA	≤ 50
√ Cloud point (10% in BDG at 25%)	EN 1890	°C	76 – 78
Hydroxyl number	EN 13926	mg KOH / g	100 – 108
Molecular weight	Calculated	g/mol	519 – 561
Polyethylene glycols	EN 12582	% mass	≤ 3,0
√ pH (5%)	EN 1262	-	5,0 – 7,0
√ Free Water (Karl Fischer)	ASTM E203	% mass	≤ 0,50

√ value reported on inspection certificate.

¹ specification No. 1950 rev. 2 of May 25th 2022.

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content	Calculated	%w/w	64
HLB	Calculated	-	12,9
Pour point	ASTM D97	°C	12
Viscosity at 40°C	ASTM D7042	cSt	36
Viscosity at 50°C	ASTM D7042	cSt	25
Density at 50°C	ASTM D7042	kg/m ³	980
Flash point	ASTM D 93	°C	> 125

**sasol**

TRIDAC ISO-8

Technical Data Sheet No. 1654 – March 2023

Main Applications

TRIDAC ISO-8 can be used as degreasing agent in wool scouring process and leather treatment and as emulsifier in agrochemical applications.

In the detergency field TRIDAC ISO-8 is used in HDP formulations due to its high emulsification property at medium-low temperature.

In metal working field TRIDAC ISO-8 shows good dispersing properties for chip or shaving particles as well as good emulsification behaviour regarding to the most common lubricating oils used.

Handling and Storage

TRIDAC ISO-8 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

TRIDAC ISO-8 is a cloudy liquid at room temperature and it becomes a solid wax at temperature lower than 22°C. Improvement of appearance and handling at low temperature can be achieved by mixing the product with 15 weight% water to obtain a clear liquid up to a temperature about 5 °C.

At room temperature TRIDAC ISO-8 is not water soluble.

Over time the product can settle generating different layers of inhomogeneous material. This is not a sign of poor product quality, but it is a common feature of many non-ionic surfactants.

Products that have begun to precipitate should be reconstituted by gentle heating, at about 40°C, and mixing. The temperature must not be allowed to exceed 50°C.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

TRIDAC ISO-8 is generally supplied in drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of companies, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

The information contained in this document is based on Sasol's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products. All our business transactions are governed exclusively by our General Business Terms.