




ISALCHEM[®] 11-8-85%

Technical Data Sheet No. 1193 – November 2012

Description

ISALCHEM[®] 11-8-85% is a fatty alcohol polyethyleneglycol ether, based on ISALCHEM[®] 11 and ethylene oxide (8 moles) that is diluted with 15% of water. It is manufactured in Terranova dei Passerini (Lodi, Italy) plant. The chemical structure is the following:



CAS registry no. 127036-24-2

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
* Appearance at 25°C	visual	-	clear liquid
* Colour ⁺	MPL 1002.0	APHA	≤ 50
* Cloud point ^{a+}	MPL 2001.0	°C	60-62
* pH (5% in water) ⁺	MPL 1007.0	-	5.0 - 7.0
* Water (Karl-Fisher)	MPL 1006.0	% w/w	14 - 16

⁺ values referred to the product not diluted

* values reported on inspection certificate.

¹ specification No. D001451 rev. 1 of April 16th, 2002.

^a 1 wt% water solution.

Additional Properties

Property	Test Method	Unit	Typical Value
Density at 40°C	RCM 3663.1	Kg/l	1.01
Viscosity at 40°C	RCM 3633.1	cSt	41
Puor point	RCM 3629	°C	-18
Ethylene Oxide content ⁺	calculated	% w/w	67
HLB ⁺	calculated	-	13.3
Average Molecular Mass ⁺	calculated	g/mol	524
Physical state changement ⁺	MPL 1001.1	°C	10
Flash point ⁺	RCM 3628	°C	> 125

⁺ values referred to the product not diluted

RCM and MPL are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



ISALCHEM[®] 11-8-85%

Technical Data Sheet No. 1193 – November 2012

Main Applications

ISALCHEM[®] 11-8-85% is a good wetting agent with degreasing performance. It can be used as detergent product in the textile field, as degreasing agent in leather treatment and in metal working application. It is suitable for NPE 9 replacement.

Handling and Storage

ISALCHEM[®] 11-8-85% should preferably be stored in heated stainless steel tanks. It is a homogeneous and transparent at room temperature. It is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena. At low temperature ISALCHEM[®] 11-8-85% remains liquid and handling up to a temperature of -15°C. Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

ISALCHEM[®] 11-8-85% is generally supplied in drums, details on available packaging can be obtained from sales department.

Cod. 20462

Distribuito da:
Tellerini S.p.A.
Via Bonazzi, 36
40013 Castel Maggiore (BO) IT
Tel. +39 051 6322111 Fax +39 051 715380
sito: www.tellerini.it mail: info@tellerini.it

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support

Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

The information and data presented in this sheet represent our best knowledge of the products, but are not a guarantee of the performance of their derivatives, since the conditions of use are not under our direct control. Furthermore, nothing indicated herein should be considered as a guideline to the use of the product, particularly should this result in infringement of any patent right of manufacture or use ISALCHEM[®] is a Sasol Italy S.p.A. trademark.