



Distribuito da:



Tellerini s.p.a.

Via Bonazzi, 36  
40013 Castel Maggiore (BO)  
Tel: +39 051 6322111  
Fax: +39 051 715380  
[sicurezza@tellerini.it](mailto:sicurezza@tellerini.it)  
[www.tellerini.it](http://www.tellerini.it)


# LIALET 125-9

Technical Data Sheet No. 1706 – November 2015

sasol

## Product Description

LIALET 125-9 is a fatty alcohol polyethyleneglycol ether, based on LIAL 125 and ethylene oxide (about 9 moles). It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



CAS registry no. 106232-83-1  
EINECS no. 932-186-2  
INCI C12-15 PARETH-9

## Sales Specification

Property	Test Method	Unit	Guaranteed Value <sup>1</sup>
√ Appearance at 25°C	Visual	-	Fluid paste
√ Colour	MPL 1002.0	APHA	≤ 50
√ Cloud point (1% in water)	MPL 2001.0	°C	60 – 62
√ pH (5%)	MPL 1007.0	-	5,0 – 7,0
√ Free Water (Karl Fischer)	MPL 1006.0	% mass	≤ 0,50

√ value reported on inspection certificate.

<sup>1</sup> specification No. 2680 rev. 1 of February 6<sup>th</sup> 2003.

## Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content	Calculated	%w/w	66
HLB	Calculated	-	13,1
Hydroxyl number	EN 13926	mg KOH / g	93
Molecular weight	Calculated	g/mol	603
Polyethylene glycols	EN 12582	% mass	≤ 3,0
Pour point	ASTM D 97	°C	22
Viscosity at 40°C	ASTM D445 / ASTM D7042	cSt	39
Viscosity at 50°C	ASTM D445 / ASTM D7042	cSt	26
Density at 40°C	ASTM D7042 / ASTM D4052	kg/m <sup>3</sup>	988
Flash point	ASTM D 93	°C	> 125

RCM and MPL are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.

**sasol**

# LIALET 125-9

Technical Data Sheet No. 1706 – November 2015

---

## Main Applications

LIALET 125-9 can be used as detergent product in the wool scouring process, as degreasing in leather treatment, as emulsifier in agrochemicals and agriculture applications.

In metal working field LIALET 125-9 shows good dispersing properties for chip or shaving particles as well as good emulsification behaviour regarding to the most common lubricating oils used.

In the detergency field LIALET 125-9 is used in HDP formulations due to its high emulsification property at medium-low temperature.

---

## Handling and Storage

LIALET 125-9 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

LIALET 125-9 is a paste at room temperature and it becomes clear liquid at temperature about 50°C.

LIALET 125-9 becomes a solid wax at temperature lower than 22°C. Improvement of appearance and handling at low temperature can be achieved by mixing the product with 5 to 15 weight% water.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

---

## Packaging

LIALET 125-9 is generally supplied in drums, details on available packaging can be obtained from sales department.

---

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

---

### Sasol Italy S.p.A.

Headquarters  
Viale Forlanini, 23  
20134 Milano, Italy  
Phone +39-02 58453 1  
Fax +39-02 58453 285

Technical Customer Support  
Via E. Mattei, 4  
26827 Terranova dei Passerini (LO), Italy  
Phone +39-0377 463 1  
Fax +39-0377 463 226

This information is based on our present knowledge and experience. but it is not a guarantee of the performance of our products since the conditions of use are not under our direct control.

However, it implies no liability or other legal responsibility on our part, including any existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. All our business transactions shall be governed exclusively by our General Sales Conditions.

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of Companies. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved.