



SASOL

MARLIPAL 31-1085

Technical Data Sheet No. 1205 – February 2021

Product Description

MARLIPAL 31-1085 is a fatty alcohol polyethyleneglycol ether, based on C11 branched and linear- C13 branched alcohol and ethylene oxide (about 10 moles) and diluted with 15 weight% water. It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



EINECS no. 949-938-0
 INCI C11-13 PARETH-10

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	Visual	-	Clear liquid
√ Colour	MPL 1002.0	APHA	≤ 50
√ Cloud point (1% in water) (+)	MPL 2002.0	°C	64 – 66
√ pH (5%) (+)	MPL 1007.0	-	5,0 – 7,0
√ Free Water (Karl Fischer)	MPL 1006.0	% mass	14,0 – 16,0

√ value reported on inspection certificate.

¹ specification No. 1977 rev. 2 of February 5th 2007.

(+) values referred to the product not diluted

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content (+)	Calculated	%w/w	68
HLB (+)	Calculated	-	13,6
Hydroxyl number (+)	EN 13926	mg KOH / g	93
Average Molecular weight (+)	Calculated	g/mol	603
Polyethylene glycols (+)	EN 12582	% mass	1,5
Pour point	ASTM D97	°C	- 18
Density at 25°C	ASTM D7042	kg/m ³	1.018
Density at 40°C	ASTM D7042	kg/m ³	990
Viscosity kinematic at 25°C	ASTM D7042	mm ² /s	119
Viscosity dynamic at 40°C	ASTM D7042	mPas	54
Flash point	ASTM D 93	°C	> 125

RCM are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



MARLIPAL 31-1085

Technical Data Sheet No. 1205 – February 2021

Further information

Heavy metal

Arsenic (As) less than 1 mg/kg	Cadmium (Cd) less than 1 mg/kg
Cobalt (Co) less than 1 mg/kg	Chromium (Cr) less than 1 mg/kg
Copper (Cu) less than 1 mg/kg	Iron (Fe) less than 2 mg/kg
Manganese (Mn) less than 1 mg/kg	Nickel (Ni) less than 1 mg/kg
Lead (Pb) less than 1 mg/kg	Tin (Sn) less than 1 mg/kg
Strontium (Sr) less than 1 mg/kg	Zinc (Zn) less than 1mg/kg

Heavy metal content is periodically checked (ICP method); data given here have to be considered as typical.

Preservative

MARLIPAL 31-1085 does not contain any preservative. MARLIPAL 31-1085 is not susceptible to microbial growth because of low water content.

Property	Test Method	Unit	Typical Value
Total Aerobic Microbial Count	Eu.Ph. 5.1.4	CFU/g	< 100
Total Yeasts/Moulds Count	Eu.Ph. 5.1.4	CFU/g	< 10

Microbiological control test is periodically done; data given here have to be considered as typical.

Antioxidants

MARLIPAL 31-1085 does not contain any antioxidant.

Pesticides

MARLIPAL 31-1085 does not contain any pesticide.

Product origin

MARLIPAL 31-1085 is manufactured from following raw materials:

- Alcohols C₁₁ and C₁₃ branched with synthetic origin
- Ethylene oxide with synthetic origin

Main Applications

MARLIPAL 31-1085 can be used as degreasing agent in leather treatment and as emulsifier in agrochemical applications.

In metal working field MARLIPAL 31-1085 shows good dispersing properties for chip or shaving particles as well as good emulsification behaviour regarding to the most common lubricating oils used.

In the textile field MARLIPAL 31-1085 can be used as detergent surfactant.

MARLIPAL 31-1085 is suitable for NPE 10 replacement.



SASOL

MARLIPAL 31-1085

Technical Data Sheet No. 1205 – February 2021

Handling and Storage

MARLIPAL 31-1085 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

MARLIPAL 31-1085 is a clear liquid at room temperature it becomes a solid wax at temperature lower than minus 18°C.

At room temperature MARLIPAL 31-1085 is water soluble up to 30 weight%.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

MARLIPAL 31-1085 is generally supplied in plastic drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of companies, except where it is clear from the context that not. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved. Reference to trademarks used by other companies is neither a recommendation, nor should it give the impression that products of other companies cannot be used.

The information contained in this document is based on Sasol's knowledge and experience at the time of its creation. We reserve the right to make any changes to this document or the products described therein, as a result of technological progress or developments. This information implies no liability or other legal responsibility on our part, including with regard to existing third-party patent rights. In particular, no guarantee or warranty of properties in the legal sense is implied. The customer is not exempted from the obligation to conduct careful inspection and testing of incoming products. All our business transactions are governed exclusively by our General Business Terms.