



Distribuito da:



Tellerini s.p.a.

Via Bonazzi, 36
40013 Castel Maggiore (BO)
Tel: +39 051 6322111
Fax: +39 051 715380
sicurezza@tellerini.it
www.tellerini.it


MARLIPAL 31-90

Technical Data Sheet No. 1202 – March 2019

SASOL

Product Description

MARLIPAL 31-90 is a fatty alcohol polyethyleneglycol ether, based on C11 branched and linear- C13 branched alcohol and ethylene oxide (about 9 moles). It is manufactured in Terranova dei Passerini (LO) plant. The chemical structure is the following:



EINECS no. 949-938-0
INCI C11-13 PARETH-9

Sales Specification

Property	Test Method	Unit	Guaranteed Value ¹
√ Appearance at 25°C	Visual	-	Cloudy liquid
√ Colour	RCM 3668	APHA	≤ 50
√ Cloud point (1% in water)	RCM 3646	°C	54 – 56
√ pH (5%)	RCM 3645	-	5,0 – 7,0
√ Free Water (Karl Fischer)	RCM 3804	% mass	≤ 0,50

√ value reported on inspection certificate.

¹ specification No. 1972 rev. 2 of January 29th 2007.

Additional Properties

Property	Test Method	Unit	Typical Value
Ethylene Oxide content	Calculated	%w/w	66
HLB	Calculated	-	13,2
Hydroxyl number	EN 13926	mg KOH / g	100
Average Molecular weight	Calculated	g/mol	561
Polyethylene glycols	EN 12582	% mass	1,5
Pour point	ASTM D97	°C	25
Viscosity at 50°C	ASTM D445 / ASTM D7042	cSt	25
Density at 50°C	ASTM D7042 / ASTM D4052	kg/m ³	980
Flash point	ASTM D 93	°C	> 125

RCM and MPL are Sasol Italy analytical methods, internal or referred to international standard. Additional information available upon request.



SASOL

MARLIPAL 31-90

Technical Data Sheet No. 1202 – March 2019

Main Applications

MARLIPAL 31-90 can be used as degreasing agent in leather treatment and as emulsifier in agrochemical applications.

In metal working field MARLIPAL 31-90 shows good dispersing properties for chip or shaving particles as well as good emulsification behaviour regarding to the most common lubricating oils used.

In the textile field MARLIPAL 31-90 can be used as detergent surfactant.

MARLIPAL 31-90 is suitable for NPE 9 replacement.

Handling and Storage

MARLIPAL 31-90 should preferably be stored in stainless steel tanks.

It is suggested to keep the product at temperature below 40°C, it is preferable to avoid heating above 60°C and to store under nitrogen in order to minimise yellowish phenomena.

MARLIPAL 31-90 is a cloudy liquid at room temperature it becomes a solid wax at temperature lower than 25°C. Improvement of appearance and handling at low temperature can be achieved by mixing the product with 15 weight% water to obtain a clear liquid up to a temperature about -2 C°.

At room temperature MARLIPAL 31-90 is water soluble up to 30 weight%.

Shelf-life is 36 months from production date for product in its original and sealed packaging.

Packaging

MARLIPAL 31-90 is generally supplied in drums, details on available packaging can be obtained from sales department.

Data regarding safety, transport classes, toxicology and biodegradability of the product can be obtained from the corresponding material safety data sheet.

Sasol Italy S.p.A.

Headquarters
Viale Forlanini, 23
20134 Milano, Italy
Phone +39-02 58453 1
Fax +39-02 58453 285

Technical Customer Support
Via E. Mattei, 4
26827 Terranova dei Passerini (LO), Italy
Phone +39-0377 463 1
Fax +39-0377 463 226

This information is based on our present knowledge and experience. but it is not a guarantee of the performance of our products since the conditions of use are not under our direct control.

However, it implies no liability or other legal responsibility on our part, including any existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. All our business transactions shall be governed exclusively by our General Sales Conditions.

Sasol is a registered trademark of Sasol Ltd. Product trademarks displayed in this document are the property of the Sasol Group of Companies. Users of this document are not permitted to use these trademarks without the prior written consent of their proprietor. All rights not expressly granted are reserved.